

DECLARATION OF PERFORMANCE

CPR/01/BW/2017

1. Unique identification code of the product-type:
Multi-layer parquet elements – Type 01
2. Type, batch or serial number or any other element allowing identification of the construction products as required pursuant to Article 11(4) :

The identification code of the article is on the underside of each element.

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

*Product for the indoor private or public usage as a floor.
Installed as a floating parquet or glued to the subfloor.*

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Multilayer parquet elements Baltic Wood manufactured by
Baltic Wood S.A.
ul. Fabryczna 6a
38-200 Jasło
Poland

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

-

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

Declaration of the essential characteristics of the construction product.

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

PN-EN 14342:2013-11

Wood Technology Institute in Poznan, as a notified body number 1583, has performed the initial inspection of factory and of factory production control and performs the continuous surveillance, assessment and evaluation of factory production control system 3 and issued a Certificate of Conformity No. 0548/2016.

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not applicable

9. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire linked with: - density - thickness	D _f -s1 min. 500 kg/m ³ min. 10 mm	TM PN-EN 14342:2013-11
Emission of formaldehyde	Class E1	
Content of pentachlorophenol	NPD	
Release of other dangerous substances	NPD	
Slipperiness	Semi-matt lacquer 58 Matt lacquer 46 ECO oil 78 Oil UV 72	
Thermal conductivity	Product 10,5 mm 0,09 W/mK Product 13,3 mm 0,11 W/mK Product 14,0 mm 0,12 W/mK Product 21,0 mm 0,16 W/mK	
Biological durability	Class 1	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the Manufacturer by:

Jaslo, 2017-06-02

Rafał Zawierucha
CEO